





LABdex



-60°C Upright Freezer LX5031UF



Email: info@labdex.com **website:** www.labdex.com



Description

-60°C Upright Freezer LX5031UF offers substantial storage space for different medical products. It is an environmentally friendly device with an adjustable temperature range of -25°C to -60°C. Designed with a microprocessor control system with LED display. The external chamber is made up of sprayed steel plate and the internal material is made up of 304 stainless steel. It has various types of alarms, such as a high or low-temperature alarm and a sensor failure alarm.

Specifications

External size (W x D x H)	540 x 620 x 1115 mm
Internal size (W x D x H)	361 x 405 x 406 mm
Capacity	58 L
Temp. range	-25°C ~ -60°C, adjustable
Temp. accuracy	0.1°C
Control system	microprocessor control, LED digital display
Audible and visual alarm	High and low temperature alarm, sensor failure alarm
Refrigeration type	Optimized auto-cascade refrigerating system
Refrigerant	Unique fluoride-free mixed refrigerant, CFC-Free
Condenser & Evaporator	Optimized evaporation and condensation system, Strong cooling and low energy consumption
Internal material	304 stainless steel

External material	Sprayed steel plate
Consumption	450 W
Power supply	AC110V/220V±10%,50/60Hz
Package size (W x D x H)	610 x 690 x 1280 mm
Gross weight	105 kgs

Features

- ✓ Microprocessor control system with LED display
- ✓ It contains a 90mm ultra-thick foam layer
- ✓ It has strong cooling and low energy consumption
- ✓ Designed with an optimized auto-cascade refrigerating system
- ✓ Unique fluoride-free mixed refrigerant, CFC-Free
- ✓ It has an optimized evaporation and condensation system

Applications

- ✓ Used for storage of biological, pharmaceuticals, plasmas, research institutions, and other temperature-sensitive material in laboratories and blood banks.



71-75 Shelton Street Covent Garden, London WC2H 9JQ UK.

Email: info@labdex.com | Website: www.labdex.com